

Special Adhesive / Evertack[®]

Evertack is a special adhesive and high viscosity substance developed by ENEOS's proprietary technology using Polybutene and polyisobutylene as raw materials.

Evertack is a highly stable substance under normal conditions and is a liquid-solid polymer that is odorless, non-toxic and consistent.

Packaging	Drum, Oil Can (15kg)
Main Application	Pest / small animal capture (mouse catchers, etc.) Dry cell sealant

Table Grades and Representative Properties of EVERTACK

グレード GRADE 項目 ITEM	SA-50E	SA-400E	J-4053E	E-475	試験法 Test Method
用途 Application	小生物および害虫捕獲材 Small organisms and pests capturing material			乾電池封口材 Dry cell sealant	—
外 観 Appearance	白色 White	白色 White	白色 White	赤色 Red	JXE4239*
接着力(gf・mm, Φ7mm) Adhesive strength	1700	4700	1200	—	—
耐フロー性(60°C, 24h) Anti-flow characteristics	合格 Pass	合格 Pass	合格 Pass	—	JXE4244*
引火点 (COC.°C) Flash point	210	240	240	220	EGTM013*
粘度(at 160°C, mPa.S) Coefficient of viscosity	300	450	170	200	JXTG019*
密度 (15°C. g/cm ³) Density	0.89	0.89	0.89	0.89	JISK-2249
流動点 (°C) Pour point	80	85	85	85	EGTM009*

記載のグレードは一般グレードであります。ご要望により特殊グレードの提供も可能です。

The grades shown are general grades. We may offer special grades are upon request.

*Test Method : ENEOS Internal Test Method