## **SAFETY DATA SHEET**

#### 1. IDENTIFICATION

**PRODUCT IDENTIFIER** 

Product Name: HIMOL 6H
Reference Number: 91175

**SUPPLIER'S DETAILS** 

Name ENEOS Materials Corporation

Address 1-5-2 Higashi-shimbashi Minato-ku, Tokyo 105-7109 Japan

**Phone** +81-(0)3-6685-3651

Contact Sales & Marketing Dept.3 Group2

**Emergency Phone Number** +81-(0)3-6685-3651

(Available time; 9:00am - 5:00pm JST on Monday - Friday)

RECOMMENEDED USE OF THE CHEMICAL

Chemical basestock

AND REATRICTIONS OF USE

Chewing Gum base and Industrial use only.

#### 2. HAZARDS IDENTIFICATION

This material is not hazardous according to regulatory guidelines (see SDS Section 15).

#### OTHER HAZARDS WHICH DO NOT RESULT IN CLASSIFICATION:

## **Physical/Chemical Hazards**

Thermal burn hazard - contact with hot material may cause thermal burns.

#### **Health Hazards**

High-pressure injection under skin may cause serious damage.

#### **Environmental Hazards**

No additional hazards.

**Note:** Contact with hot material can cause thermal burns.

This material should not be used for any other purpose than the intended use in Section 1 without expert advice. Health studies have shown that chemical exposure may cause potential human health risks which may vary from person to person.

#### 3. COMPOSITION / INFORMATION ON INGREDIENTS

This material is defined as a substance.

Hazardous Constituent(s) Contained in Complex Substance(s)

Name	CAS RN®	Concentration*	GHS Hazard Codes
Polyisobutylene	9003-27-4	100 %	-

<sup>\*</sup> All concentrations are percent by weight unless material is a gas. Gas concentrations are in percent by volume. Concentration values may vary.

#### 4. FIRST-AID MEASURES

#### **DESCRIPTION OF NECESSARY FIRST-AID MEASURE**

#### Inhalation

Remove from further exposure. If respiratory irritation, dizziness, nausea, or unconsciousness occurs,

seek immediate medical assistance. If breathing has stopped, assist ventilation with a mechanical device or use mouth-to-mouth resuscitation. When mouth-to-mouth resuscitation, responder should be careful to not expose material. For those providing assistance, avoid exposure to yourself or others. Use adequate respiratory protection.

#### Skin contact

For hot product: Immediately immerse in or flush affected area with large amounts of cold water to dissipate heat. Cover with clean cotton sheeting or gauze and get prompt medical attention.

#### Eye contact

Flush thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical attention.

#### Ingestion

No adverse effects due to ingestion are expected.

#### MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE AND DALAY

Contact with hot material can cause thermal burns.

#### INDICATION OF MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED, IF NECESSARY

None

#### 5. FIRE-FIGHTING MEASURES

#### **EXTINGUISHING MEDIA**

Suitable Extinguishing Media: Foam, dry chemical, carbon dioxide (CO2)

Inappropriate Media: Straight streams of water

#### SPECIFIC HAZARDS ARISING FROM THE CHEMICALS

**Specific Hazards Arising from the Chemicals:** Combustible When heated, material can decompose and release flammable gas that readily form flammable mixtures. Firefighters should consider protective equipment indicated in Section 8.

Hazardous Combustion Products: Incomplete combustion products, carbon monoxide, smoke, fume

#### SPECIFIC PROTECTIVE ACTIONS FOR FIRE-FIGHTERS

#### Specific protective actions for fire-fighter:

Firefighters should use standard protective equipment and in enclosed spaces, self-contained breathing apparatus (SCBA). Use water spray to cool fire exposed surfaces and to protect personnel.

#### Fire Fighting Instructions:

Evacuate non-emergency personal to safe area. Extinguish fire with appropriate media. Stop leak if you can do it without risk. Use water spray or fog for cooling tanks or containers surround fire. If a leak or spill has not ignited, use water spray to disperse the vapors and to protect personnel attempting to stop a leak or to move container. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply.

#### 6. ACCIDENTAL RELEASE MEASURES

## PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

Avoid contact with spilled material. Warn or evacuate occupants in surrounding and downwind areas if required due to toxicity or flammability of the material. See Section 5 for fire fighting information. See the Hazard Identification Section for Significant Hazards. See Section 4 for First Aid Advice. See Section 8 for advice on the minimum requirements for personal protective equipment. Additional protective measures may be necessary, depending on the specific circumstances and/or the expert judgment of the emergency responders.

For emergency responders: Respiratory protection: half-face or full-face respirator with filter(s) for spilled material and, when applicable, Self Contained Breathing Apparatus (SCBA) can be used depending on the size of spill and potential level of exposure. If the exposure cannot be completely characterized or an oxygen deficient atmosphere is possible or anticipated, SCBA is recommended.

If contact with hot material is likely, thermally protective work gloves are recommended. Chemical goggles are recommended if splashes or contact with eyes is possible. Small spills: normal antistatic work clothes are usually adequate. Large spills: full body suit of antistatic material is recommended.

#### **Notification Procedures**

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations. Material is combustible. Evacuate non-emergency personal to safe area.

#### **ENVIRONMENTAL PRECAUTIONS**

No additional information

#### METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP

Land Spill: Stop leak if you can do it without risk. Do not touch or walk through spilled material. Liquid Spills: Collect with pump. If liquid is too viscous for pumping, scrape it up with shovels into a suitable container for recycle or disposal. Dry Spills: With clean shovel place material into clean, dry container Water Spill: Stop leak if you can do it without risk. Confine the spill immediately with booms. Warn other shipping. Remove from the surface by skimming.

Water spill and land spill recommendations are based on the most likely spill scenario for this material; however, geographic conditions, wind, temperature, (and in the case of a water spill) wave and current direction and speed may greatly influence the appropriate action to be taken. For this reason, local experts should be consulted. Note: Local regulations may prescribe or limit action to be taken.

#### 7. HANDLING AND STORAGE

#### PRECAUTIONS FOR SAFE HANDLING

When heating, material may release flammable gases. Use only with adequate ventilation. Prevent small spills and leakage to avoid accident.

When heating to normal handling temperatures, avoid handling at more than local 150 °C or overheating as material may release flammable decomposition products. Use only with adequate ventilation, when heating material.

Avoid contact with hot material.

## CONDITION FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

Store material less than 150°C. Do not localheat containers of material. Do not store in open or unlabelled containers.

Suitable Materials and Coatings (Chemical Compatibility): Cardboard, Stainless Steel, Steel Unsuitable Materials and Coatings: No additional information

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

## **CONTROL PARAMETERS**

Occupational exposure limits/standards (Note: Exposure limits are not additive)
Not allocated

#### **Biological limit values**

No biological limits allocated

NOTE: Limits/standards shown for guidance only. Follow applicable regulations.

#### **APPROPRIATE ENGINEERING CONTROLS**

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Control measures to consider: No special requirements under ordinary conditions of use and with adequate ventilation.

#### INDIVIDUAL PROTECTION MEASURES, SUCH AS PERSONAL PROTECTIVE EQUIPMENT (PPE)

Personal protective equipment selections vary based on potential exposure conditions such as applications,

handling practices, concentration and ventilation. Information on the selection of protective equipment for use with this material, as provided below, is based upon intended, normal usage. Any specific protective equipment information provided is based on published literature and protective equipment manufacturer data.

#### **Eye/Face Protection:**

If contact is likely, safety face protections are recommended.

#### **Skin and Body Protection:**

The types of clothing to be considered for this material include: Thermally protective chemical resistant clothing (non-permeable) is recommended.

#### **Respiratory Protection:**

If engineering controls do not maintain airborne contaminant concentrations at a level which is adequate to protect worker health, an approved respirator may be appropriate. Respirator selection, use, and maintenance must be in accordance with regulatory requirements, if applicable. Types of respirators to be considered for this material include: for mist/dust

For high airborne concentrations, use an approved supplied-air respirator, operated in positive pressure mode. Supplied air respirators with an escape bottle may be appropriate when oxygen levels are inadequate, if concentration is high, gas/vapor warning properties are poor, or if air purifying filter capacity/rating may be exceeded.

#### **Hand Protection:**

Use suitable protective glove. Glove suitability and breakthrough time will differ depending on the specific use conditions. Contact the glove manufacturer for specific advice on glove selection and breakthrough times for your use conditions. Inspect and replace worn or damaged gloves. The types of gloves to be considered for this material include:

When handling hot materials, thermally protective, chemical resistant gloves are recommended. If contact with forearms is likely, wear gauntlet style gloves.

**Specific Hygiene Measures:** Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

#### **ENVIRONMENTAL CONTROLS**

Comply with applicable environmental regulations limiting discharge to air, water and soil. Protect the environment by applying appropriate control measures to prevent or limit emissions.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Note: Physical and chemical properties are provided for safety, health and environmental considerations only and may not fully represent product specifications. Contact the Supplier for additional information.

Physical State:Semi-solidColour:Colorless/Clear

Odour:NoneMelting Point/Freezing Point:No dataBoiling Point or Initial Boiling PointNo data

and Boiling Range:

Flammability: Combustible solid

Lower and Upper Explosion Limit No data

/Flammable Limits (Approximate volume % in air):

Flash Point: No data

**Auto-ignition Temperature**: 400 °C Approximately

**Decomposition Temperature:** 150 - 400 °C

pH: N/A

Kinematic Viscosity: No data @40 °C,

(39220 - 64990mm2/sec @ 200 °C)

Solubility: Negligible Partition Coefficient n-Octanol/Water (log value): No data Vapor Pressure: No tada

Density and/or Relative Density (at 20 °C): 0.91 – 0.93 g/cm³ @15°C

Relative Vapour Density (Air = 1):

Particle Characteristics: N/A

#### 10. STABILITY AND REACTIVITY

**REACTIVITY:** No reactivity under normal conditions.

**CHEMICAL STABILITY:** Stable at normal conditions.

Thermal decomposition may start at about 150°C and the product decomposes

>1 at 101 kPa

almost completely at about 400°C.

POSSIBILITY OF HAZARDOUS REACTIONS: Hazardous polymerization or reaction will not occur.

**CONDITIONS TO AVOID:** Heat >150°C, flames.

**INCOMPATIBLE MATERIALS:** Strong oxidizers

**HAZARDOUS DECOMPOSITION PRODUCTS:** Material does not decompose at ambient temperatures. When heated (>150°C), material can release decomposition products that readily form flammable mixtures.

## 11. TOXICOLOGICAL INFORMATION

Information described here are based on the data for this material, structurally similar materials and/or components.

Information	Conclusion/Remarks
Acute toxicity	
Oral	Classification not possible
No data available	
Dermal Dermal	Classification not possible
No data available	
Inhalation	Classification not possible
No data available	
Skin corrosion/irritation	Classification not possible
No data available	'
Serious eye damage/irritation	Classification not possible
No data available	·
Sensitization	
Respiratory	Classification not possible
No data available	
Skin	Classification not possible
No data available	
CMR hazard	
Germ cell mutagenicity	Classification not possible
No data available	
Carcinogenicity	Classification not possible
No data available	-
Reproductive toxicity	Classification not possible
No data available	

Additional category for effects on or via lactation No data available	Classification not possible	
Specific target organ toxicity		
Single exposure	Classification not possible	
No data available		
Repeated exposure	Classification not possible	
No data available		
Aspiration hazard		
This material is solid.	Not classified	

# OTHER INFORMATION IARC Classification: None

#### 12. ECOLOGICAL INFORMATION

Information described here are based on the data for this material, structurally similar materials and/or components.

#### **TOXICITY**

Not expected to be harmful to aquatic organisms.

## PERSISTENCE AND DEGRADABILITY

#### **Biodegradation:**

No information available for biodegradation.

#### **Hydrolysis:**

Transformation due to hydrolysis not expected to be significant.

#### Photolysis:

Transformation due to photolysis not expected to be significant.

## Atmospheric Oxidation:

No additional information

#### **BIOACCUMULATION POTENTIAL**

No information available.

## **MOBILITY IN SOIL**

No information available.

## **OTHER ADVERSE EFFECTS**

## **Hazard to the Ozone Layer**

Not expected to be harmful to ozone layer.

#### 13. DISPOSAL CONSIDERATIONS

#### **DISPOSAL METHODS**

Disposal recommendations based on material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal.

#### **Disposal Recommendations**

Product is suitable for burning in an enclosed controlled burner for fuel value or disposal by supervised incineration at very high temperatures to prevent formation of undesirable combustion products.

#### **Empty Container Warning**

Empty Container Warning (where applicable): Empty containers may contain residue and can be dangerous. Do not attempt to refill or clean containers without proper instructions. Empty containers should be completely drained and safely stored until appropriately reconditioned or disposed. Empty

containers should be taken for recycling, recovery, or disposal through suitably contractor and in accordance with governmental regulations.

#### 14. TRANSPORT INFORMATION

#### **LAND - Precautionary Transportation Measures & Conditions:**

Comply with applicable laws and regulations.

SEA (IMDG) / AIR (IATA)

UN Number: UN Proper Shipping Name: Transport Hazard Class(es): Packing Group: Environmental hazards: No
EMS Number: -

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code:

Not applicable This product is not liquid substances.

#### 15. REGULATORY INFORMATION

This material is not considered hazardous according to the Classification of Chemicals based on Globally Harmonized System of Classification and Labelling of Chemicals (GHS).

## SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS SPECIFIC FOR THE PRODUCT IN QUESTION

#### **National Laws and Regulations:**

Comply with applicable laws and regulations.

#### **16. OTHER INFORMATION**

#### N/A = Not applicable

\_\_\_\_\_\_

The information and recommendations contained herein are, to the best knowledge and belief of ENEOS Corporation, accurate and reliable as of the date issued. You can contact ENEOS Materials Corporation to insure that this document is the most current available from ENEOS Materials Corporation. The information and recommendations are offered for the user's consideration and examination. It is the user's responsibility to satisfy itself that the product is suitable for the intended use. If buyer repackages this product, it is the user's responsibility to insure proper health, safety and other necessary information is included with and/or on the container. Appropriate warnings and safe-handling procedures should be provided to handlers and users. Alteration of this document is strictly prohibited. Except to the extent required by law, re-publication or retransmission of this document, in whole or in part, is not permitted.